



DOT SIZE
SCALE: 5:1

SPECIFICATION:

- 1). Driving: Duty: 1/16, Bias: 1/5, Vdd: 5.0V, Vlcd: 4.5V
- 2). VIEWING DIRECTION: 6 O'CLOCK
- 3). Display mode: STN /Negative /Transmissive /Blue
- 3). Operating temp.: $0^{\circ}C \sim +50^{\circ}C$
- 4). Storage temp.: $-10^{\circ}C \sim +60^{\circ}C$
- 5). Control IC: SPLC780D1 (Or Compatible)
- 6). BACKLIGHT: EDGE, WHITE (2DICES)
- 7). DIMENSIONS WITH MARK "*" ARE IMPORTANT WITH MARK "(" ARE REFERENCED
- 8). All the raw materials are RoHS compliant

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
VSS	VDD	V _O	RS	W/R	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	BLA	BLK

REVISION RECORD		REV	Shenzhen TCC 液晶科技有限公司 Shenzhen TCC LCD Hi-Tech Co., Ltd	
First issue	A0			



DRAWING NO.	SYB1602AV30-5C10BL-BSNG	GENERAL TOL:	± 0.2
-------------	-------------------------	--------------	-----------

APPROVED BY	CHECKED BY	DRAWING BY	UNIT:	mm	PAGE
-------------	------------	------------	-------	----	------

		YJQ			1/1
		2010/10/14			